



WASHDOWN PUMP KIT

Features & Benefits

- Positive displacement pump
- Can Run Dry
- Quiet operation
- Demand pump
- Easy connect fittings
- Ignition protected
- Industry Standard mount pattern

PUMP

- Liquid Temperature**
140°F (60°C) Max.
- Priming Capabilities**
6 feet (1.8 m) suction lift
- Inlet/Outlet Ports**
1/2" -14MNPT
- Weight**
8.2 lbs (3.72 kg) -51 series

INCLUDES

- (1) 3.0/5.0 GPM Heavy-Duty Washdown Pump
- (2) Trigger Spray Nozzle w/Quick Connect
- (3) 25' Coiled Hose(UV Protected, 1/2")
- (4) Quick Hose Disconnect Fitting
- (5) 50 Mesh Inlet Strainer
- (6) 1/2" Barbed Fittings



More details and other optional accessories

STANDARD PUMP CONFIGURATIONS

Model	Voltage	Switch	GPM/LPM	PSI/BAR	Max Draw(A)	Valves	Diaphragm	Ports	Wire Connections
700035219	12 V	Demand	5.0/18.9	70/4.8	18	EPDM	Santoprene	1/2"-14 MPNT	2-Pin/Leads
700035220	24 V	Demand	5.0/18.9	70/4.8	9	EPDM	Santoprene	1/2" -14 MPNT	2-Pin/Leads